4022, 4025A, BOP-1000, TW-5W, TW-7W, WP-1
Interconnects and Splitters

Features

4022
1 x 2 25 pair, 50-pin passive splitter. Used to interconnect two 800 Series master stations or 4000 Series IFB system control panels.

4025A
1 x 4 25 pair, 50-pin passive splitter. Used to connect multiple 800 Series master stations or 4000 Series IFB systems control panels.

BOP-1000
Black 19" blank mounting rack. Required for mounting: TW-7W

TW-5W
1 x 5 Two channel 3-pin XLR type Passive Splitter. Features a rugged metal box for portable floor interconnect.

TW-7W
One female XLR-3 into seven male XLR-3 out (½ rack wide)

WP-1
Single Channel Wall Plate-Male XLR-3 type connector.

Line Drawing

4022 4025A   BOP-1000   TW-5W   TW-7W   WP-1

Interconnects and Splitters Specifications

4022

1 x 2 25 pair, 50-pin passive splitter. Used to interconnect two 800 Series master stations or 4000 Series IFB system control panels.

4025A

1 x 4 25 pair, 50-pin passive splitter. Used to connect multiple 800 Series master stations or 4000 Series IFB systems control panels.

BOP-1000

Black 19" blank mounting rack. Required for mounting TW-7W

TW-5W

1 x 5 Two channel 3-pin XLR type Passive Splitter. Features a rugged metal box for portable floor interconnect.

TW-7W

One female XLR-3 into seven male XLR-3 out (½ rack wide)

WP-1

Single Channel Wall Plate-Male XLR-3 type connector.

Contact Information

Telex Communications, Inc.
12000 Portland Avenue South
Burnsville, Minnesota 55337
Telephone: (800) 392-0498
Fax: (800) 323-0498

Form Number: 38110488
Date: March, 2006